

GROUTING UNITS

model T.A.D. 40

FOR CEMENT GROUT, CHEMICAL GROUT, OTHER MIXTURES



Is designed to meet particularly the problems of consolidation works, micro piling, anchor hole and where valves pipes fracture system is concerned (HP-LP). All machines are properly placed on a single iron welded base for easy operation and prompt site setting.

Grouting unit T.A.D. 40 consists of:

- High-speed mixer mod. TM 260, capacity tank 200 litres – 7,3 kW electric motor
- Agitator mod. A 500, capacity tank 450 litres – 2,2 kW electric motor
- Grouting pump mod. DPOL4 RGM electro-hydraulic, delivery BP 40 litres min. – pressure 40 bar max, delivery HP 9 litres min. – pressure 85 bar max, 3 kW electric motor.

CLIVIO supply a complete line of machines for THE WHOLE GROUTING WORK: drill units, grout pumps, high speed mixers and all accessories.

Machine	Total capacity Litre		Work capacity Litre		rpm/min.	Electric motor kW
TM260	240		200		1450	7,5
A500	500		450		97	2,2
Machine	Max delivery litre/min.		Max pressure bar		Electric motor kW	
	AP	BP	AP	BP		
DP/OL-4 RGM	9	40	85	40	3	
Length mm.	Width mm.		Height mm.		Weight Kg.	Maximum flow and pressure values cannot be reached simultaneously
3100	1130		1750		930	

(All data, illustrations and features of this prospectus are subject to change without notice or liability)