

GROUT INJECTION UNIT

mod. **MP/A-2 - MA200A**

FOR CEMENT GROUT, CHEMICAL GROUT AND OTHER MIXTURE



Grout injection units CLIVIO mod. MP/A-2-MA200A have been designed to meet the technical requirements of the customer and are configured to satisfy the specific operational requirements.

Grouting units MP/A-2-MA200A consist of:

- M200A – Mixer CLIVIO air driven
- A200A – Agitator CLIVIO air driven
- MP/A-2 – Pump (injector) CLIVIO air driven.

All machines of the grout injection unit are arranged in a functional way on a single base frame (on request with 4 jack, rubber wheels and parking brake) and centralized control panel to be ready for use.

Particularly suitable in those sites where the compressed air is available at low cost.

The use of a group so compact and light greatly reduces the installation time on site and requires minimal maintenance.

CLIVIO supply a complete line of machines for the **WHOLE GROUTING WORK**: drill units, grout pumps, high speed mixers and all accessories.

Model	Total capacity litres	Work capacity litres	Speed vertical shaft rpm	Air driven kW
M200A	220	200	130	1,1
A200A	220	200	130	1,1
Model	Piston diameter mm.	Maximum delivery l/min.	Maximum pressure bar	Maximum flow and pressure values cannot be reached simultaneously
MP/A-2	50 / 60 / 70 / 80	28 / 41 / 55 / 72	60 / 42 / 31 / 23	
Lenght mm.	Width mm.	Height mm.	Weight kg.	Air consumption at 7 bar litri/min.
1900	1420	1500	670	4350

(All data descriptions and designs in this brochure are subject to change without notice or responsibility)