

## GROUT INJECTION UNIT

mod. **AP/OL-S – ETA**

mod. **AP/OL-90S – ETA**

FOR GROUT INJECTION AND SPECIAL MIXTURE



Groups injection CLIVIO mod. AP / OL-S-ETA or AP/OL-90S-ETA have been designed to meet the technical requirements of the customer and are configured to satisfy the specific operational requirements.

Grouting units APOL-S-ETA and APOL-90S-ETA consist of:

- High Speed Mixer CLIVIO mod. TM-260 with electric motor.
  - Agitator CLIVIO mod. A-750R with electric motor reduction gear.
  - Grout Injection Pump CLIVIO mod. APOL-S-ETA or APOL-90S-ETA with electric motor.
  - Electric panel
  - Steel welded frame for installation of above mentioned machines with 4 lifting points.
- On request the units can be mounted on rubber wheels.

CLIVIO supply a complete line of machines for THE WHOLE GROUTING WORK: drill units, grout pumps, high speed mixers and all accessories.

Model	Total capacity Liters	Work capacity Liters	Shaft speed Rpm	Electric motor kW
TM260	240	200	1450	7,5
A750	810	750	87	3
Model	Piston diameter mm.	Maximum delivery L/min.	Maximum pressure Bar	Electric motor kW
AP/OL-S	50 / 60 / 70 / 80	31 / 45 / 61 / 80	120 / 110 / 100 / 77	11
AP/OL-90S		54 / 78 / 106 / 138	105 / 92 / 67 / 52	15
Lenght mm.	Width mm.	Height mm.	Weight Kg.	Maximum flow and pressure values cannot be reached simultaneously.
3450	1750	1750	1800	

(All the data, illustrations and characteristics of the present prospect are subject to changes without warning neither responsibility)