

GROUTING UNIT DIESEL DRIVEN

mod. **APOL.SP-DHTA**

FOR CEMENT GROUT AND SPECIAL GROUT



Grout injection unit CLIVIO mod. APOL.SP-DHTA diesel driven consisting of:

- TM 260-High speed mixer CLIVIO hydraulic driven
- A750R - Agitator CLIVIO with hydraulic motor
- APOL-SP – Grouting injection pump
- Hydraulic power pack including Diesel engine HATZ SILENT PACK 32.3 kW, oil tank, air oil-cooler, hydraulic gear pumps
- Hydraulic panel including hand operated lever distributors for ON/OFF APOL.SP, TM260, A750R oil max pressure valve, oil pressure gauge
- Steel welded frame for installation of above mentioned machines with 4 lifting points.

CLIVIO supply a complete line of machines for THE WHOLE GROUTING WORK: drill units, grout pumps, high speed mixers and all accessories.

Model	Max vol Litres	Working vol. Litres	Shaft turning max Rpm.	Diesel engine kW
TM260i	240	200	1450	32,3
A750i	810	750	87	
Model	Piston diameter mm.	Max delivery l/min.	Max pressure Bar	
AP/OL-SP	80	80	110	Maximum flow and pressure values cannot be reached simultaneously.
Length mm.	Width mm.	Height mm.	Weight kg.	
3500	2000	1800	2400	

(All data descriptions and designs in this brochures are subject to change without notice nor responsibility.)