

## ELECTRIC GROUT INJECTION UNIT

# model **MP/OL-2 - ETA 130**

## FOR CEMENT GROUT AND SPECIAL GROUTS



The Group injection unit CLIVIO model MP/OL-2-ETA 130 is consisting of:

- High Speed Mixer CLIVIO model TM130 electrical driven,
- Agitator CLIVIO model A200 electrical driven,
- Pump (injector) CLIVIO model MP/OL-2 electro-hydraulic driven.
- Electric panel

on a single iron welded steel frame.

All machines of the grout injection unit are arranged in a functional way on a single base frame (on request with 4 jack, rubber wheels and parking brake) and centralized control panel to be ready for use.

Particularly suitable in those sites where the compressed air is available at low cost.

The use of a group so compact and light greatly reduces the installation time on site and requires minimal maintenance.

CLIVIO supply a complete line of machines for the **WHOLE GROUTING WORK**: drill units, grout pumps, high speed mixers and all accessories.

Model	Total capacity litres	Work capacity litres	Shaft speed rpm	Electric motor kW
TM130	130	100	1450	3
A200	220	200	130	1,1
Model	Pistons diameter mm.	Maximum delivery litres/min.	Maximum pressure bar	Electric motor kW
MP/OL-2	50 / 60 / 70 / 80	28 / 39 / 54 / 70	120 / 82 / 61 / 46	7,5
Length mm.	Width mm.	Height mm.	Weight kg.	Maximum flow and pressure values cannot be reached simultaneously.
2310	1430	1560	970	

(All the data, illustrations and characteristics of the present prospect are subject to changes without warning neither responsibility)