

AIR DRIVEN GROUT INJECTOR UNIT

model **MP/A-2 – PTA130**

FOR CEMENT GROUT, CHEMICAL GROUT AND OTHER MIXTURES



The Grout Injection Unit CLIVIO model MP/A-2 – PTA130 is composed of:

- TM130A – Highspeed mixer CLIVIO air driven
- A200A - Agitator CLIVIO air driven
- MP/A-2 – Pump (injector) CLIVIO air driven

All machines of the grout injection unit are arranged in a functional way on a single base frame (on request with 4 jack, rubber wheels and parking brake - see photo) and centralized control panel to be ready for use.

Particularly suitable in those sites where the compressed air is available at low cost.

The use of a group so compact and light greatly reduces the installation time on site and requires minimal maintenance. CLIVIO supply a complete line of machines for THE WHOLE GROUTING WORK: drill units, grout pumps, high speed mixers and all accessories.

Model	Total capacity liters	Work capacity liters	Speed vertical shaft rpm	Air driven kW
TM130A	130	100	1450	3
A200A	220	200	130	1,1
Model	Grout pistons diameter mm.	Max grout delivery liters/min.	Max grout pressure bar	Maximum flow and pressure values cannot be reached simultaneously
MP/A-2	50 / 60 / 70 / 80	28 / 41 / 55 / 72	60 / 42 / 31 / 23	
Length mm.	Width mm.	Height mm.	Weight kg.	Air consumption at 7 bar liters/min.
2420*	1820*	1800*	750*	6350

* Dimensions and weight are of the version with option wheels.

(All data, illustrations and features of this prospectus are subject to change without notice or liability)