

GROUTING UNIT DIESEL - HYDRAULIC DRIVEN

mod. **T.A.D. 40 – 130 DH**

FOR CEMENT GROUT AND SPECIAL GROUT



Grout injection unit CLIVIO mod. T.A.D.40-130 DH consisting of:

- TM130-High speed mixer CLIVIO hydraulic driven
- A200 - Agitator CLIVIO with hydraulic motor
- DP/OL-4 RGM – Vertical grouting pump
Our grouting pump mod.DPOL-4 can work for mini-piles injections, tunnel liner grouting, rock anchor grouting, void filling etc.....

- Hydraulic power pack including Diesel engine 18.8 kW, oil tank, air oil-cooler, hydraulic gear pumps

- Hydraulic panel including hand operated lever distributors for ON/OFF TM130, A200 oil max pressure valve, oil pressure gauge

- Steel welded frame for installation of above mentioned machines with 4 lifting points.

CLIVIO supply a complete line of machines for THE WHOLE GROUTING WORK: drill units, grout pumps, high speed mixers and all accessories.

Model	Max. vol Litri	Working vol. litri	Shaft turning max rpm.		Liquid cooled Diesel engine Lombardini LDW 1003 NA 18.8 KW
TM130	130	100	1500		
A200	220	200	130		
Model	Max delivery Lt./min.		Grout pressure bar		Maximun flow and pressure values cannot be reached simultaneously.
	AP	BP	AP	BP	
DP/OL-4 RGM	9	40	85	40	
length mm.	width mm.	height mm.	weight Kg.		
2500	1650	1600	1000		

(All data descriptions and designs in this brochures are subject to change without notice nor responsibility.)